

RAVENOL Motobike 4-T Standard 20W-50

Вискозност: 20W-50

Минерално уље



1 л

Чланак:

1173133-001

Чланак:

1173133-001-01-999



4 л

Чланак:

1173133-004

Чланак:

1173133-004-01-999

With **RAVENOL Motobike 4-T Standard SAE 20W-50** a solid and high loadable engine oil was developed for superior engines of motorbikes with wet couplings and oil lubricated couplings.

RAVENOL Motobike 4-T Standard SAE 20W-50 has an excellent lubricating film adhesive capacity and a very good shear stability as well as an excellent cleaning power and a high aging resistance.

Application Note

RAVENOL Motobike 4-T Standard SAE 20W-50 is suitable as an engine oil for all motorbikes from year 2001 in case the specification SAE 20W-50 JASO MA/MA2 is requested.

Characteristics

- Good shear stability
- Good cold start characteristics
- High oxidation stability
- Stable lubricating film even under heavy load
- Prevention of black sludge formation
- Very good viscosity-temperature behavior
- Convincing detergent and dispersant properties
- High safety reserves, even with boundary lubrication conditions
- Very low evaporation tendency

Карактеристике

Име	Значење	Ревизија
API	SL	
JASO	MA, MA2	
Густина на 20°C	879 г/цм ³	EN ISO 12185
Боја	Жуто-браон	visual
Вискозност на 100°C	18.8 мм ² /с	DIN 51562-1
Вискозност на 40°C	174.6 мм ² /с	DIN 51562-1
Индекс вискозности VI	121	DIN ISO 2909
Тачка стињавања	-24 °C	DIN ISO 3016
Волатилност NOACK	3.4 %	ASTM D5800
Температура паљења	258 °C	DIN EN ISO 2592
Основни број	6.7 мгКОХ/г	ASTM D2896
Садржај сулфатног пепела	0.82 %wt.	DIN 51575

Укинуто паковање

Паковање	Чланак	Баркод
4 л	1173133-004-01-999	