

RAVENOL Hydraulikoel TS 10 (HLP)

Вискозност: 10

Минерално уље



1 л

Чланак:
1323101-001



5 л

Чланак:
1323101-005



20 л

Чланак:
1323101-020
Чланак:
1323101-020-01-999
Баркод:
4014835741126



20 л, есобох

Чланак:
1323101-B20



60 л

Чланак:
1323101-060



208 л

Чланак:
1323101-208



1 000 л

Чланак:
1323101-700

RAVENOL Hydraulikoel TS 10 (HLP) with efficient additives offers an excellent corrosion protection even under extreme loads. The behaviour of sealing materials is neutral.

RAVENOL Hydraulikoel TS 10 (HLP) is characterised by good viscosity temperature behaviour, a high aging resistant and a solid corrosion protection.

Application Note

RAVENOL Hydraulikoel TS 10 (HLP) is for universally use in all hydraulic systems.

RAVENOL Hydraulikoel TS 10 (HLP) is recommended in high performance hydraulic systems with high pressure pumps of all types, in sensitive control systems.

RAVENOL Hydraulikoel TS 10 (HLP) is used for hydraulic systems in agriculture, to supply small gearboxes and for use in circulating systems.

Characteristics

- a high performance level
- a very good viscosity temperature behaviour
- a high aging resistant
- an excellent corrosion protection
- a solid corrosion protection
- mainly neutrality of sealing materials

Карактеристике

Име	Значење	Ревизија
ASTM	D6158	
Испуњава захтеве	AFNOR NFE 48-603 HM, Bosch Rexroth RE 90220, Cetop RP 91H HM, Cincinnati Milacron P-69, Cincinnati Milacron P-70, Cincinnati Milacron 3-68, Danieli Hydraulics, FZG Test A 8,3/90, ISO 11158 HM, MIL-H-24459, Parker Denison HF-0, Parker Denison HF-2, SAE MS 1004 HM, Sauer-Danfoss 520L0463, VDMA 24318, Vickers Pumpentest	
Испуњава спецификације	DIN 51524-2, ISO 6743-4 HM	
Погодан за	Metso	
Густина на 20°C	833 г/цм ³	EN ISO 12185
Боја	Светло жуто	visual
Вискозност на 100°C	2.7 мм ² /с	DIN 51562-1
Вискозност на 40°C	9.9 мм ² /с	DIN 51562-1
Индекс вискозности VI	110	DIN ISO 2909
Тачка стињавања	-36 °Ц	DIN ISO 3016
Температура паљења	190 °Ц	DIN EN ISO 2592

Укинуто паковање

Паковање	Чланак	Баркод
1 л	1323101-001-01-999 1323101-001-06-999	
5 л	1323101-005-01-999	
60 л	1323101-060-01-999	
208 л	1323101-208-01-999	