

# RAVENOL Frostlube F 12

Синтетички



#### 20 л

Чланак: **1323350-020** Чланак: 1323350-020-01-999



#### 20 л, ecobox

Чланак: **1323350-B20** 



#### 60 л

Чланак: **1323350-060** 



#### 208 л

Чланак: **1323350-208** 

**RAVENOL Frostlube F 12** is a high quality, anti-wear hydraulic oil with a very high viscosity index, good shear stability and excellent low-temperature properties.

### **Application Note**

**RAVENOL Frostlube F 12** is excellently suitable for application in extremely low temperatures, e.g. equipment in refrigerated warehouses or mobile facilities, which are used outdoors under extreme winter conditions.

**RAVENOL Frostlube F 12** is specifically formulated so that a consistent viscosity is extensively given even in the case of extremely varying temperatures.

**RAVENOL Frostlube F 12** is a shear stable, high quality hydraulic oil and therefore, suitable for application under extreme hydraulic conditions without risk for the system. If the oil temperature is permanently above 80°C, the hydraulic system should be pressurised to minimise oil loss due to evaporation.

### **Characteristics**

- An extremely high viscosity index so that the good lubrication properties and the protection in the eventof minimal viscosity alterationss are ensured by a wide temperature range.
- A low pour point; therefore, application at extremely low temperatures is permitted without the risk offreezing.
- An extremely good resistance to oxidation and a very good shear stability; therefore, longer service lifeof the oil under the usually extreme application conditions.
- Protection of the hydraulic system against corrosive influences.
- Anti-wear effect.
- Load bearing capability.
- Longer service life of the oil.

## Карактеристике

Име	Значење	Ревизија
Испуњава спецификације	ISO 6743-4 HV	
Густина на 20°Ц	828 g/cm³	EN ISO 12185
Боја	Зелен	visual
Вискозност на 100°С	6.7 mm²/s	DIN 51562-1
Вискозност на 40°С	19.9 mm²/s	DIN 51562-1
Индекс вискозности VI	332	DIN ISO 2909
Тачка стињавања	-49 °C	DIN ISO 3016
Температура паљења	172 °C	DIN EN ISO 2592

# Укинуто паковање

Паковање	Чланак	Баркод
60 л	1323350-060-01-999	
208 л	1323350-208-01-999	