

RAVENOL Frostlube F 22

Минерално уље



1 л

Чланак:
1323351-010



208 л

Чланак:
1323351-208

RAVENOL Frostlube F 22 is a high quality, anti-wear hydraulic oil with a very high viscosity index, good shear stability and excellent low-temperature properties.

Application Note

RAVENOL Frostlube F 22 is excellently suitable for application in extremely low temperatures, e.g. equipment in refrigerated warehouses or mobile facilities, which are used outdoors under extreme winter conditions.

RAVENOL Frostlube F 22 is specifically formulated so that a consistent viscosity is extensively given even in the case of extremely varying temperatures.

RAVENOL Frostlube F 22 is a shear stable, high quality hydraulic oil and therefore, suitable for application under extreme hydraulic conditions without risk for the system. If the oil temperature is permanently above 80°C, the hydraulic system should be pressurized to minimize oil loss due to evaporation.

Characteristics

- An extremely high viscosity index so that the good lubrication properties and the protection in the event of minimal viscosity alterations are ensured by a wide temperature range.
- A low pour point; therefore, application at extremely low temperatures is permitted without the risk of freezing.
- An extremely good resistance to oxidation and a very good shear stability; therefore, longer service life of the oil under the usually extreme application conditions.
- Protection of the hydraulic system against corrosive influences.

- Anti-wear effect.
- Load bearing capability.
- Longer service life of the oil.

Карактеристике

Име	Значење	Ревизија
Испуњава спецификације	ISO 6743-4 HV	
Густина на 20°C	837 г/цм ³	EN ISO 12185
Боја	Зелен	visual
Вискозност на 100°C	7.3 мм ² /с	DIN 51562-1
Вискозност на 40°C	25.4 мм ² /с	DIN 51562-1
Индекс вискозности VI	274	DIN ISO 2909
Тачка стињавања	-63 °Ц	DIN ISO 3016
Температура паљења	156 °Ц	DIN EN ISO 2592

Укинуто паковање

Паковање	Чланак	Баркод
1 л	1323351-010-01-999	
208 л	1323351-208-01-999	