

RAVENOL Vakuumpumpenöl ISO VG 150

Вискозност: 150

Минерално уље



20 л

Чланак:
1330708-020
Чланак:
1330708-020-01-999



20 л, еcobox

Чланак:
1330708-B20



60 л

Чланак:
1330708-060
Чланак:
1330708-060-01-999



208 л

Чланак:
1330708-208
Чланак:
1330708-208-01-999

Application Note

RAVENOL Vakuumpumpenöl ISO VG 150 is suitable for the lubrication of vacuum pumps (rotary vane pumps, diffusion pumps, turbo pumps), where mineral oils are required, as well as for mist lubrication and crankcase.

RAVENOL Vakuumpumpenöl ISO VG 150 oil pumps can be used very well for the lubrication of crankcases. This vacuum pump oil should not be used in systems with silver or silver alloys.

Characteristics

- High performance level
- Very good viscosity-temperature behavior
- High resistance to aging
- Excellent wear protection
- Reliable corrosion protection

- Very good oxidation stability
- Very good demulsification
- Excellent air release, which largely eliminates foam formation
- Neutral from over plastic seals
- Low pour point

Карактеристике

Име	Значење	Ревизија
Испуњава захтеве	AFNOR NFE 48-603 HM, AFNOR NFE 48-603 HV, Vickers Vane Pump	
Испуњава спецификације	DIN 51506 VC, DIN 51524-2	
Густина на 20°C	886 г/цм ³	EN ISO 12185
Боја	Светло браон	visual
Вискозност на 100°C	14.6 мм ² /с	DIN 51562-1
Вискозност на 40°C	150 мм ² /с	DIN 51562-1
Индекс вискозности VI	95	DIN ISO 2909
Тачка стињавања	-21 °Ц	DIN ISO 3016
Температура паљења	240 °Ц	DIN EN ISO 2592
Киселински број, ТАН	0.4 мг KOH/г	ASTM D664
Садржај сулфатног пепела	0.06 %wt.	DIN 51575